


Datasheet

M.2 (S42) 3IE4 series

- SATA III solution for industrial field
- Exclusive L³ architecture
- Designed with hardware LDPC ECC engine
- Supported iData Guard protection
- DRAM-less, 100% data integrity
- Excellent random performance
- Supported TRIM/NCQ/SMART



Introduction

Innodisk M.2 (S42) 3IE4 is characterized by **L³ architecture with the latest SATA III** (6.0GHz) Marvell NAND controller. Innodisk's exclusive L³ architecture is L² architecture multiplied LDPC (Low Density Parity Check). L² (Long Life) architecture is a 4K mapping algorithm that reduces WAF and features a real-time wear leveling algorithm to provide high performance and prolong lifespan with exceptional reliability.

Innodisk M.2 (S42) 3IE4 is designed for industrial field, and supports several standard features, including TRIM, NCQ, and S.M.A.R.T. In addition, Innodisk's exclusive industrial-oriented firmware provides a flexible customization service, making it perfect for a variety of industrial applications.

M.2 (S42) 3IE4 series

Diagram

**Contact us for more information
about the M.2 (S42) 3IE4.**

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi
Dist., New Taipei City 221, Taiwan
Tel: +886-2-7703-3000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-40-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2017 Innodisk Corporation.
All right reserved. Specifications are
subject to change without
prior notice.

Specifications

Interface	SATA III
Flash Type	iSLC
P/E cycle	20,000
Capacity	8GB~128GB
Max. Channels	2
Sequential R/W (MB/sec, max.)	530/380
Max. Power Consumption	1.5W (3.3V x 460 mA)
Thermal Sensor	✓
External DRAM buffer	-
H/W Write Protect	Optional
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	22.0 X 42.0 X 3.2 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

20210223

Ordering Information

Operation Temp.	8GB	16GB	32GB	64GB	128GB
Industrial Grade (-40°C ~ +85°C)	RS-INO- M2B2242-8SI	RS-INO- M2B2242-16SI	RS-INO- M2B2242-32SI	RS-INO- M2B2242-64SI	RS-INO- M2B2242-128SI
Tested and approved for use with WINSYSTEMS embedded computers					



www.innodisk.com